

		RIM recommended Inches	WIDTH mm (Inches) Unmounted	DIAMETER mm (Inches) Unmounted	WARM PSI (Cold PSI) Suggested	WARMERS °C (°F)
2024 RANGE						
DIABLO SUPERBIKE SLICKS						
10" Slick	<i>front 100/80-10</i>	2.50	104 (4.09)	435 (17.13)	22/23 (19/20)	30 - 60 mins 70°- 80°C (158 - 176°F)
	<i>rear 120/80-10</i>	3.00	122 (4.80)	451 (17.76)	20/22 (17/19)	
12" Slick	<i>front 100/90-12</i>	2.50	102 (4.02)	490 (19.29)	22/23 (19/20)	
	<i>rear 120/80-12</i>	3.00	120 (4.72)	501 (19.72)	20/22 (17/19)	
Moto3	<i>front 100/70 R17</i>	2.50	101 (3.98)	580 (22.83)	26/29 (25/28)	30 - 60 mins 70°- 80°C (158 - 176°F)
	<i>rear 120/70 R17</i>	3.50	120 (4.72)	604 (23.77)	25/28 (23/26)	
17"	<i>front 110/70 R17</i>	3.00	112 (4.42)	590 (23.22)	29/33 (26/30)	
	<i>front 120/70 R17</i>	3.50	120 (4.72)	604 (23.77)	32/36 (29/33)	
	<i>front 125/70 R17</i>	3.50	124 (4.88)	610 (24.02)	32/36 (29/33)	
	<i>rear 140/70 R17</i>	4.00	141 (5.55)	628 (24.72)	24/26 (21/23)	
	<i>rear 160/60 R17</i>	4.50	165 (6.50)	631 (24.84)	25/28 (22/25)	
	<i>rear 180/55 R17</i>	5.50	181 (7.12)	641 (25.23)	25/28 (22/25)	
	<i>rear 180/60 R17</i>	5.50	190 (7.48)	656 (25.82)	23/26 (20/23)	
	<i>rear 190/60 R17</i>	5.50	195 (7.48)	662 (26.06)	25/28 (22/25)	
<i>rear 200/60 R17</i>	6.00	200 (7.87)	662 (26.06)	23/26 (20/23)		
<i>rear 200/65 R17</i>	6.00	202 (7.95)	672 (26.45)	25/28 (22/25)		
DIABLO SUPERCORSA DOT						
17" Diablo Supersorsa SC3	<i>front 110/70 ZR17</i>	2.75-3.00	112 (4.42)	590 (23.22)	29/34	15 - 30 mins 40-50°C (104-122°F)
	<i>front 120/70 ZR17</i>	3.50	120 (4.72)	604 (23.77)	32/36	
	<i>rear 140/70 ZR17</i>	3.50-4.00	141 (5.55)	628 (24.21)	25/28	
	<i>rear 160/60 ZR17</i>	4.50	165 (6.50)	631 (24.84)	25/28	
	<i>rear 180/55 ZR17</i>	5.50	184 (7.24)	641 (25.23)	25/28	
	<i>rear 180/60 ZR17</i>	5.50	190 (7.48)	656 (25.82)	24/27	
	<i>rear 200/55 ZR17</i>	6.00	193 (7.60)	656 (25.82)	25/28	
	<i>rear 200/60 ZR17</i>	6.00	200 (7.87)	670 (26.37)	25/28	
DIABLO RAINS						
10" Rain	<i>front 100/80-10</i>	2.50	104 (4.09)	435 (17.13)	22/23 (19/20)	15 - 30 mins 40-50°C (104 - 122°F)
	<i>rear 120/80-10</i>	3.00	122 (4.80)	451 (17.76)	22/23 (19/20)	
12" Rain	<i>front 100/90-12</i>	2.50	102 (4.02)	490 (19.29)	22/23 (19/20)	
	<i>rear 120/80-12</i>	3.00	120 (4.72)	496 (19.53)	22/23 (19/20)	
17"	<i>front 110/70 R17</i>	3.00	112 (4.42)	590 (23.22)	32 (29)	
	<i>front 120/70 R17</i>	3.50	120 (4.72)	604 (23.81)	35 (32)	
	<i>rear 140/70 R17</i>	4.00	140 (5.51)	628 (24.72)	29 (26)	
	<i>rear 160/60 R17</i>	4.50	172 (6.77)	635 (25.00)	29 (26)	
<i>rear 200/60 R17</i>	5.50/6.00	200 (7.87)	662 (26.06)	29 (26)		